AU OPTRONICS CORPORATION

Product Specification

19.0" SXGA Color TFT-LCD Module

Model Name: M190EN04 V.3

Approved by	Prepared by
CC Chiu	*Winni Chen*

DDBU Marketing Division / AU Optronics corporation

Customer	Checked & Approved by

Product Specification

19.0" SXGA Color TFT-LCD Module
Model Name: M190EN04
V.3

(∪) Preliminary Specifications
( ) Final Specifications

Note: This Specification is subject to change without notice.

Contents

Record of Revision

Version and Date	Page	Old description	New Description	Remark
0.1 2004/08/01	All	First Edition for Customer	All	

1.0 Handling Precautions

1) Since front polarizer is easily damaged, pay attention not to scratch it.

2) Be sure to turn off power supply when inserting or disconnecting from input connector.

3) Wipe off water drop immediately. Long contact with water may cause discoloration or spots.

4) When the panel surface is soiled, wipe it with absorbent cotton or other soft cloth.

5) Since the panel is made of glass, it may break or crack if dropped or bumped on hard surface.

6) Since CMOS LSI is used in this module, take care of static electricity and insure human earth when handling.

7) Do not open nor modify the Module Assembly.

8) Do not press the reflector sheet at the back of the module to any directions.

9) In case if a module has to be put back into the packing container slot after once it was taken out from the container, do not press the center of the CCFL reflector edge. Instead, press at the far ends of the CCFL reflector edge softly. Otherwise the TFT module may be damaged.

10) At the insertion or removal of the Signal Interface Connector, be sure not to rotate nor tilt the Interface Connector of the TFT module.

11) After installation of the TFT module into an enclosure (Desktop monitor Bezel, for example), do not twist nor bend the TFT Module even momentary. At designing the enclosure, it should be taken into consideration that no bending/twisting forces are applied to the TFT module from outside.   Otherwise the TFT module may be damaged.

2.0 General Description

This specification applies to the 19.0 inch Color TFT-LCD Module M190EN04.

The display supports the SXGA (1280(H) x 1024(V) screen format and 262K colors (RGB 6-bits).

All input signals are 2 Channel LVDS interface compatible.

This module does not contain an inverter card for backlight.

2.1 Display Characteristics

The following items are characteristics summary on the table under 25 ℃ condition:

ITEMS	Unit	SPECIFICATIONS
Screen Diagonal	[mm]	480(19")
Active Area	[mm]	376.32 (H) x 301.056 (V)
Pixels H x V		1280(x3) x 1024
Pixel Pitch	[mm]	0.294 (per one triad) x 0.294
Pixel Arrangement		R.G.B. Vertical Stripe
Display Mode		Normally White
White Luminance (Center)	[cd/m^2]	250 cd/m2 @7mA (Typ)
Contrast Ratio		450 : 1 (Typ)
Optical Response Time	[msec]	16ms (Typ, on/off)
Nominal Input Voltage VDD	[Volt]	+5.0 V
Power Consumption (VDD line + CCFL line)	[Watt]	28W(Typ) (w/o Inverter, All black pattern) (PDD=7.5 W, PCFL=19.6 W @Lamp=7.0mA)
Weight	[Grams]	2700 (Max)
Physical Size	[mm]	396(W) x 324(H) x 18(D) (Typ)
Electrical Interface		R/G/B data, Clock
Support Color		262k colors (RGB 6-bit data)
Surface Treatment		Glare, Hard Coating, 2H
Temperature Range Operating Storage (Shipping)	[^{o}C] [^{o}C]	0 to +50 -20 to +60

Product Specification

2.2 Optical Characteristics

The optical characteristics are measured under stable conditions at 25℃:

| Item	Unit	Conditions		Min.	Typ.	Max.	Note
Viewing Angle	[degree] [degree]	Horizontal (Right) CR = 10 (Left)		65 65	70 70	- -	
	[degree] [degree]	Vertical (Up) CR = 10 (Down)		65 60	70 65	- -	
		Horizontal (Right) CR = 5 (Left)			>80 >80		
		Vertical (Up) CR = 5 (Down)			>80 >80		
Contrast ratio		Normal Direction		250	450		
Response Time	[msec]	Raising Time		-	4	5	*Note 1*
	[msec]	Falling Time		-	12	20	*Note 1*
	[msec]	Raising + Falling		-	16	25	*Note 1*
Color / Chromaticity Coordinates (CIE)		Red x		0.604	0.634	0.664	
		Red y		0.324	0.354	0.384	
		Green x		0.27	0.3	0.33	
		Green y		0.585	0.615	0.645	
		Blue x		0.108	0.138	0.168	
		Blue y		0.047	0.077	0.107	
Color Coordinates (CIE) White		White x		0.28	0.31	0.34	
		White y		0.30	0.33	0.36	
White Luminance at CCFL 7.0mA (central point)	[cd/m^2]			200	250	-	
Luminance Uniformity	[%]			70	75	-	*Note 2*
Crosstalk (in75Hz)	[%]					1.5	*Note 3*
Flicker	dB					-20	*Note 4*
TC0-03 Compliance							*Note 5*

Equipment   Pattern Generator, Power Supply, Digital Voltmeter, Luminance meter (PR 880, BM-5A ,

BM 7 ,CS-1000, & EZContrast*)

Aperture   1° with 100cm VD or 2° with 50cm viewing distance
Test Point   Center (VESA point 9)
Environment   < 1   lux

LCD Module

PR-880 /
BM5A /
BM7

measuring distance

Module Driving Equipment

*' EZ Contrast is different measurement tool with very close viewing distance.

Note 1: **Definition of Response time**

The output signals of photodetector are measured when the input signals are changed from "Black" to "White" (rising time), and from "White" to "Black "(falling time), respectively. The response time is interval between the 10% and 90% of amplitudes.

% Tr_F Tr_R

100
90

Optical
response   White   Black   White

10
0

Note 2: **Brightness uniformity of these 9 points is defined as below**

$$\text{Uniformity} = \frac{\text{Minimum Luminance in 9 points (1-9)}}{\text{Maximum Luminance in 9 Points (1-9)}}$$

Note 3: Crosstalk is defined as below :

Unit: percentage of dimension of display area

0 gray level

l L_A-$L_{A'}$ l / L_A x 100%= 1.5% max., L_A and L_B are brightness at location A and B

l L_B-$L_{B'}$ l / L_B x 100%= 1.5% max., $L_{A'}$ and $L_{B'}$ are brightness at location A' and B'

Note 4: Test Paterm: Subchecker Pattern

R	G	B	R	G	B
R	G	B	R	G	B
R	G	B	R	G	B

☐ Gray Level = L127

▨ Gray Level = L0

Method: Record dBV & DC value with (WESTAR)TRD-100

Amplitude

AC

DC

Time

$$\text{Flicker (dB)} = 20\log \frac{\text{AC Level(at 30 Hz)}}{\text{DC Level}}$$

Note5: Tuning the brightness and contrast function in OSD let the luminance to 125 cd/m^2. When tuning the brightness to 125cd/m^2, the function on OSD should not restrict our V-T curve. In other word, the higher contrast, the range of panel's V-T curve will be more extensive to get the better performance. If it is not possible to achieve the test luminance by this procedure it is suitable to tune contrast higher and brightness lower.

3.0 Functional Block Diagram

The following diagram shows the functional block of the 19.0 inches Color TFT/LCD Module:

JAE   FI-XB30SSL-HF15

Mating Type: FI-X30HL

JST   BHSR-02VS-1

Mating Type: SM02B-BHSS-1-TB

4.0 Absolute Maximum Ratings

Absolute maximum ratings of the module is as following:

4.1 TFT LCD Module

Item	Symbol	Min	Max	Unit	Conditions
Logic/LCD Drive Voltage	VIN	+4.5	+5.5	[Volt]	*Note 1,2*

4.2 Backlight Unit

Item	Symbol	Min	Max	Unit	Conditions
CCFL Current	ICFL	-	7.5	[mA] rms	*Note 1,2*

4.3 Absolute Ratings of Environment

Item	Symbol	Min	Max	Unit	Conditions
Operating Humidity	HOP	8	95	[%RH]	*Note 3*
Storage Temperature	TST	-20	+60	[^{o}C]	*Note 3*
Storage Humidity	HST	8	95	[%RH]	*Note 3*

Note 1: With in Ta (25℃)

Note 2: Permanent damage to the device may occur if exceed maximum values

Note 3: For quality perfermance, please refer to AUO IIS(Incoming Inspection Standard).

Relative Humidity %

5.0 Electrical characteristics

5.1 TFT LCD Module

5.1.1 Power Specification

Input power specifications are as follows;

Symbol	Parameter	Min	Typ	Max	Units	Condition
VDD	Logic/LCD Drive Voltage	4.5	5	5.5	[Volt]	±10%
IDD	VDD current	-	1500	1900	[mA]	Vin=5V, All Black Pattern, at 75Hz. +30%,for max.
Irush	LCD Inrush Current	-	-	2.5	[A]	*Note*
PDD	VDD Power	-	7.5	10	[Watt]	Vin=5V, All Black Pattern, at 75Hz. +30%,for max.
VDDrp	Allowable Logic/LCD Drive Ripple Voltage			100	[mV] p-p	
VDDns	Allowable Logic/LCD Drive Ripple Voltage			100	[mV] p-p	

Note: Measurement conditions:

Vin rising time

5.1.2 Signal Electrical Characteristics

Input signals shall be low or Hi-Z state when Vin is off
It is recommended to refer the specifications of SN75LVDS82DGG (Texas Instruments) in detail.

Each signal characteristics are as follows;

Symbol	Parameter	Min	Typ	Max	Units	Condition
VTH	Differential Input High Threshold	-	-	+100	[mV]	VICM = 1.2V *Note*
VTL	Differential Input Low Threshold	-100	-	-	[mV]	VICM = 1.2V *Note*
｜VID｜	Input Differential Voltage	100	400	600	[mV]	*Note*
VICM	Differential Input Common Mode Voltage	+1.0	+1.2	+1.35	[V]	VTH/VTL = ±100MV *Note*

Note: LVDS Signal Waveform

5.2 Backlight Unit

Parameter guideline for CCFL Inverter

Symbol	Parameter	Min.	Typ.	Max.	Unit	Condition
ISCFL	CCFL standard current	6.5	7.0	7.5	[mA] rms	(Ta=25^{o}C) *Note 1*
IRCFL	CCFL operation range	3.0	7.0	7.5	[mA] rms	(Ta=25^{o}C)
FCFL	CCFL Frequency	40	50	80	[KHz]	(Ta=25^{o}C) *Note 2*
ViCFL (0^{o}C)	CCFL Ignition Voltage (End of the lamp wire connector)	1800	-	-	[Volt] rms	(Ta=0^{o}C) *Note 3*
ViCF (25^{o}C)	CCFL Ignition Voltage (End of the lamp wire connector)	1500	-	-	[Volt] rms	(Ta=25^{o}C) *Note 3*
VCFL	CCFL Operation Voltage	-	700 @7.0mA	860 @6.5mA	[Volt] rms	(Ta=25^{o}C) *Note 4*
PCFL	CCFL Power consumption (for reference)	-	19.6	22	[Watt]	(Ta=25^{o}C) *Note 5*
LTCFL	CCFL life Time	40,000	50,000	-	[Hour]	(Ta=25^{o}C) *Note 6*

Note 1: CCFL standard current is measured at 25±2℃..

Note 2: CCFL Frequency should be carefully determined to avoid interference between inverter and TFT LCD

Note 3: ViCFL means Ignition Voltage for both ends of the lamp, and CCFL inverter should be able to give out a power that has a generating capacity of over 1800 voltage. Lamp units need 1800 voltage minimum for ignition

Note 4: CCFL operation voltage is measured at 25±2℃.

Note 5: The variance of CCFL power consumption is ±10%. Calculator value for reference

(ICFL×VCFL×4=PCFL).

Note 6: Definition of life: brightness becomes 50% or less than the minimum luminance value of CCFL..The typical life time of CCFL is on the condition at 7.0mA lamp current.

6.0 Signal Characteristic

6.1 Pixel Format Image

Following figure shows the relationship of the input signals and LCD pixel format.

6.2 The input data format

6.3 Signal Description

The module using one LVDS receiver SN75LVDS82(Texas Instruments) or compatible. LVDS is a differential signal technology for LCD interface and high speed data transfer device. Transmitter shall be SN75LVDS83(negative edge sampling) or compatible**.** The first LVDS port(RxOxxx) transmits odd pixels while the second LVDS port(RxExxx) transmits even pixels.

PIN #	SIGNAL NAME	DESCRIPTION
1	RxO0-	Negative LVDS differential data input (Odd data)
2	RxO0+	Positive LVDS differential data input (Odd data)
3	RxO1-	Negative LVDS differential data input (Odd data)
4	RxO1+	Positive LVDS differential data input (Odd data)
5	RxO2-	Negative LVDS differential data input (Odd data, H-Sync,V-Sync,DSPTMG)
6	RxO2+	Positive LVDS differential data input (Odd data, H-Sync,V-Sync,DSPTMG)
7	GND	Power Ground
8	RxOC-	Negative LVDS differential clock input (Odd clock)
9	RxOC+	Positive LVDS differential clock input (Odd clock)
10	RxO3-	Negative LVDS differential data input (Odd data)
11	RxO3+	Positive LVDS differential data input (Odd data)
12	RxE0-	Negative LVDS differential data input (Even clock)
13	RxE0+	Positive LVDS differential data input (Even data)
14	GND	Power Ground
15	RxE1-	Positive LVDS differential data input (Even data)

| 16	RxE1+	Negative LVDS differential data input (Even data)
17	GND	Power Ground
18	RxE2-	Negative LVDS differential data input (Even data)
19	RxE2+	Positive LVDS differential data input (Even data)
20	RxEC-	Negative LVDS differential clock input (Even clock)
21	RxEC+	Positive LVDS differential clock input (Even clock)
22	RxE3-	Negative LVDS differential data input (Even data)
23	RxE3+	Positive LVDS differential data input (Even data)
24	GND	Power Ground
25	NC	-
26	NC	-
27	NC	-
28	POWER	Power
29	POWER	Power
30	POWER	Power

Note1: Start from left side

Note2: Input signals of odd and even clock shall be the same timing.

6.4.1 Timing Characteristics

Basically, interface timings described here is not actual input timing of LCD module but output timing of SN75LVDS82DGG (Texas Instruments) or equivalent. **Note:** Typical value refer to VESA STANDARD

Signal	Item	Symbol	MIN	TYP	MAX	Unit
DTCLK	Freq.	Fdck	50	67.5	70	MHz
DTCLK	Cycle	Tck	14.2	14.8	20	ns
+V-Sync	Frame Rate	1/Tv	56.25	75	77	Hz
+V-Sync	Cycle	Tv	13	13.33	17.78	ms
+V-Sync	Cycle	Tv	1035	1066	2047	lines
+V-Sync	Active level	Tva	3	3		lines
+V-Sync	V-back porch	Tvb	7	38	63	lines
+V-Sync	V-front porch	Tvf	1	1		lines
+DSPTMG	V-Line	m	-	1024	-	lines
+H-Sync	Scan rate	1/Th	-	80.06	-	KHz
+H-Sync	Cycle	Th	800	844	1023	Tck
+H-Sync	Active level	Tha (*1)	4	56		Tck
+H-Sync	Back porch	Thb (*1)	4	124		Tck
+H-Sync	Front porch	Thf	4	24		Tck
+DSPTMG	Display Pixels	n	-	640	-	Tck

6.4.2 Timing diagram

6.5 Power ON/OFF Sequence

Vin power and lamp on/off sequence is as follows. Interface signals are also shown in the chart. Signals from any system shall be Hi-Z state or low level when Vin is off.

Symbol	Values			Unit
	Min	**Typ**	**Max**	
T1	0	-	10	[ms]
T2	0.5	40	50	[ms]
T3	300	-	-	[ms]
T4	300	-	-	[ms]
T5	0.5	16	50	[ms]
T6	0.5	-	10	[ms]
T7	1000	-	-	[ms]

7.0 Connector & Pin Assignment

Physical interface is described as for the connector on module.
These connectors are capable of accommodating the following signals and will be following components.

7.1 TFT LCD Module

Connector Name / Designation	Interface Connector / Interface card
Manufacturer	JAE or compatible
Type Part Number	FI-XB30SSL-HF15
Mating Housing Part Number	FI-X30HL

Pin#	Signal Name	Pin#	Signal Name
1	RxO0-	2	RxO0+
3	RxO1-	4	RxO1+
5	RxO2-	6	RxO2+
7	GND	8	RxOC-
9	RxOC+	10	RxO3-
11	RxO3+	12	RxE0-
13	RxE0+	14	GND
15	RxE1-	16	RxE1+
17	GND	18	RxE2-
19	RxE2+	20	RxEC-
21	RxEC+	22	RxE3-
23	RxE3+	24	GND
25	NC	26	NC
27	NC	28	Power
29	Power	30	Power

7.2 Backlight Unit

Connector Name / Designation	Lamp Connector / Backlight lamp
Manufacturer	JST
Type Part Number	BHSR-02VS-1
Mating Type Part Number	SM02B-BHSS-1-TB

7.3 Signal for Lamp connector

	Connector No.	Pin No.	Input	Color	Function
Upper	CN1	1	Hot1	Pink	High Voltage
		2	Cold1	White	Low Voltage
	CN2	1	Hot2	Blue	High Voltage
		2	Cold2	Black	Low Voltage
Lower	CN3	1	Hot1	Pink	High Voltage
		2	Cold1	White	Low Voltage
	CN4	1	Hot2	Blue	High Voltage
		2	Cold2	Black	Low Voltage

8.0 Vibration, Shock, and Drop

8.1 Vibration & Shock

Vibration Test Spec:

l　Frequency:　10 - 200Hz

l　Sweep:　30 Minutes each Axis (X, Y, Z)

l　Acceleration:　1.5G(10~200Hz P- P)

l　Test method:

Acceleration (G)	1.5
Frequency (Hz)	10~200~10
Active time (min)	30

Shock Test Spec:

Acceleration (G) –a	50
Active time -b	20 ms
Wave form	Half-sin
Times	1

l　Direction: ±X , ±Y, ±Z

8.2 Drop test

Package test: The drop height is 60cm.

9.0 Environment

The display module will meet the provision of this specification during operating condition or after storage or shipment condition specified below. Operation at 10% beyond the specified range will not cause physical damage to the unit.

9.1 Temperature and Humidity

9.1.1 Operating Conditions

The display module operates error free, when operated under the following conditions;

Temperature $0\ ^{0}C$ to $50\ ^{0}C$
Relative Humidity   8% to 95%
Wet Bulb Temperature $39.0\ ^{0}C$

9.1.2 Shipping Conditions

The display module operates error free, after the following conditions;

Temperature $-20\ ^{0}C$ to $60\ ^{0}C$
Relative Humidity   8% to 95%
Wet Bulb Temperature $39.0\ ^{0}C$

9.2 Atmospheric Pressure

The display assembly is capable of being operated without affecting its operations over the pressure range as following specified;

	Pressure	**Note**
Maximum Pressure	1040hPa	0m = sea level
Minimum Pressure	674hPa	3048m = 10.000 feet

Note : Non-operation attitude limit of this display module = 30,000 feet. = 9145 m.

9.3 Thermal Shock

The display module will not sustain damage after being subjected to 100 cycles of rapid temperature change. A cycle of rapid temperature change consists of varying the temperature from $-20^{0}C$ to $60^{0}C$, and back again.

Thermal shock cycle $-20\ ^{0}C$ for 30min
                                    $60\ ^{0}C$ for 30min

Power is not applied during the test. After temperature cycling, the unit is placed in normal room ambient for at least 4 hours before powering on.

10.0 Reliability

This display module and the packaging of that will comply following standards.

10.1 Failure Criteria

The display assembly will be considered as failing unit when it no longer meets any of the requirements stated in this specification. Only as for maximum white luminance, following criteria is applicable.

I   Maximum white Luminance shall be 125cd/m^2 or more.

10.2 Failure Rate

The average failure rate of the display module (from first power-on cycle till 1,000 hours later) will not exceed

1.0%. The average failure rate of the display module from 1,000 hours until 16,000 hours will not exceed

0.7% per 1000 hours.

10.2.1 Usage

The assumed usage for the above criteria is:
I   220 power-on hours per month
I   500 power on/off cycles per month
I   Maximum brightness setting
I   Operation to be within office environment (25^{0}C typical)

10.2.1 Component De-rating

All the components used in this device will be checked the load condition to meet the failure rate criteria.

10.3 On/OFF Cycle

The display module will be capable of being operated over the following ON/OFF Cycles.

ON/OFF	Value	Cycles
+Vin and CCFL power	30,000	10 seconds on / 10 seconds off

11.0 Safety

11.1 Sharp Edge Requirements

There will be no sharp edges or comers on the display assembly that could cause injury.

11.2 Materials

11.2.1 Toxicity

There will be no carcinogenic materials used anywhere in the display module. If toxic materials are used, they will be reviewed and approved by the responsible ADT Toxicologist.

11.2.2 Flammability

All components including electrical components that do not meet the flammability grade UL94-V1 in the module will complete the flammability rating exception approval process.

The printed circuit board will be made from material rated 94-V1 or better. The actual UL flammability rating will be printed on the printed circuit board.

11.3 Capacitors

If any polarized capacitors are used in the display assembly, provisions will be made to keep them from being inserted backwards.

12.0 Other requirement

## 12.1 National Test Lab Requirement

The display module will satisfy all requirements for compliance to

|	
UL 1950, First Edition	U.S.A. Information Technology Equipment
CSA C22.2 No.950-M89	Canada, Information Technology Equipment
EEC 950	International, Information Technology Equipment
EN 60 950	International, Information Processing Equipment
	(European Norm for IEC950)

12.2 Label
# The label is on the panel as shown below:

13.0 Mechanical Characteristics

SECTION D-D

SEE DETAIL 2

5
4.8
2.6

4.5

DETAIL 2
SCALE 3.000

386.8

201.4

SEE DETAIL 1

A

12.2

46.8
40.45

66.8
63.45

PIN 1   PIN 32

79.4(I/F CONNECTOR)

D   D

103.75(I/F CONNECTOR)

97.4

D   D

(2X) 93.9 Ref   CABLES MUST GO THROUGH THE CABLE HOOK FOR THE LENGTH MEASUREMENT.

108±5

0.3
THE GAP BETWEEN
BEZEL AND CELL
IS 0.8mm.

DETAIL 1
SCALE 3.000

Label Mark (recess 0.1mm)

A

SECTION A-A

This drawing is the property of AU Optronics Corp. and should not be disclosed to any third party without prior permission of AU Optronics Corp.

FORM NO. : AUPD-040-006 Ver.0

REV	ECN NO.	DESCRIPTION	SIGN	DATE
	-	-	WILLIE CHU	2003/09/03
	-	-	IVY SHIU	2004/03/09
	-	-	IVY SHIU	2004/03/18

TITLE   APPEARANCE

DRAWING NO./PART NO.   97.19M04.300

APPROVED ANDRY SU   2003/09/03
CHECKED   ANDRY SU   2003/09/03
DESIGNED WILLIE CHU 2003/09/03

AUO   AU Optronics

ORIGINAL MODEL M190EN04

SIZE A1   SHT 2-3   REV

Ver0.1

NOTE:
1. PRELIMINARY DRAWING FOR REFERENCE ONLY.
2. THE DIMENSION EXCULDES DEFORMATION.
3. MODULE THICKNESS SHOULD BE 18mm MAX.
4. TOLERENCE WITHOUT NOTICED TO BE ±0.5mm.
5. LAMP CABLE CONNECTOR TO BE JST BHSR-02VS-1
6. I/F CONNECTOR TO BE JAE FI-X30SSL-HF.
7. M3 USER HOLE SCREW TORQUE 4.0kg-cm MAX.
8. USER HOLE SCREW PENETRATION 4.5mm MAX.
9. DIMENSION TOLERENCE |A-B|≤1.0 , |C-D|≤1.0

ACTIVE AREA

BEZEL OPEN

DETAIL A
SCALE 2.000

ACTIVE AREA

BEZEL OPEN

DETAIL B
SCALE 2.000

CHECK NOTE 9

THICKNESS 18.0mm MAX IN THIS AREA

SEE DETAIL A

REAR VIEW

Label Mark (recess 0.1mm)

SCALE 0.800

FRONT VIEW

SEE DETAIL B

SCALE 0.800

REV	ECN NO.	DESCRIPTION	SIGN	DATE
⚠	-	-	WILLIE CHU	2003/09/01
⚠	-	-	IVY SHIU	2004/03/09
⚠	-	-	IVY SHIU	2004/03/19

TITLE: APPEARENCE
DRAWING NO./PART NO.: 97.19M04.300
ORIGINAL MODEL: M190EN04
AU Optronics
SIZE: A1
Sht: 3-3

FORM NO. AUPD-040-006 Ver.0